

BUBBLE MONSTER TECHNICAL DATA

PAINT COATING PRODUCTS

DETAILS		P10	B9	W9	G+
DURABILITY	BASIC	> 36 months	> 24 months	> 24 months	
	REGULAR INSPECTION	60 months / 25K km	36 months / 15K km	36 months / 15K km	12 months / 8K km
THICKNESS		0.4 ~ 0.6µm	0.3 ~ 0.5µm	0.3 ~ 0.5µm	0.3 ~ 0.5µm
HARDNESS		10H	9H	9H	8H
CONTACT ANGLE	BASIC CURING	> 100' (+-5)	> 80' (+-5)	> 110' (+-5)	> 80' (+-5)
	FINAL CURING	> 120' (+-5)	> 115' (+-5)	> 120' (+-5)	> 115' (+-5)
PH TOLERANCE		PH2 ~11	PH2 ~11	PH2 ~11	PH2 ~11
THERMAL RESISTANCE		> 1000'			

COMPONENT COATING PRODUCTS

DETAILS		Nappa	Metal	Glass	Plastic
DURABILITY	BASIC	> 24 months	> 24 months	> 7 months	> 4 months
	REGULAR INSPECTION	36 months / 15K km	36 months / 15K km	12 months / 8K km	6 months / 3K km
THICKNESS		0.3 ~ 0.5µm	0.4 ~ 0.6µm	0.3 ~ 0.5µm	0.3 ~ 0.5µm
HARDNESS		4H	9H	9H	8H
CONTACT ANGLE	BASIC CURING	> 80' (+-5)	> 110' (+-5)	> 110' (+-5)	> 110' (+-5)
	FINAL CURING	> 85' (+-5)	> 120' (+-5)	> 120' (+-5)	> 130' (+-5)
PH TOLERANCE		PH 7	PH2 ~10	PH2 ~10	PH2 ~10
THERMAL RESISTANCE			> 1500'		

BUBBLE MONSTER TECHNICAL DATA

INSTALL & MANAGEMENT

DETAILS		Vitalizer	Booster G	Booster M	Booster W
THICKNESS		0.25 ~ 0.45μm	0.2 ~ 0.4μm	0.3 ~ 0.5μm	0.2 ~ 0.4μm
CONTACT ANGLE	BASIC CURING	> 85' (+-5)	> 80' (+-5)	> 80' (+-5)	> 80' (+-5)
	FINAL CURING	> 120' (+-5)	> 115' (+-5)	> 115' (+-5)	> 115' (+-5)
PH TOLERANCE		PH2 ~11	PH2 ~11	PH2 ~11	PH2 ~11